



Heavy-duty 2" Insulated Sectional Door

Amarr® 2432

The Amarr 2432 features heavy-duty solid steel construction. Two tough steel skins and an advanced 4-step insulation system make the Amarr 2432 a strong and durable door.

The outer skin is made from 24-gauge steel and features a stucco embossment with shallow pencil grooves. The interior skin utilizes 27-gauge steel with stucco embossment.


The 4-step insulation system includes tongue and groove construction, CFC-free polystyrene insulation, weather-stripping, and a thermal break that provides a strong barrier from extreme heat and cold.



CONSTRUCTION

R-Value 9.19 Amarr 2432
Heavy-duty, 2" insulated steel door

TRIPLE-LAYER Steel + Insulation + Steel



Track: All Amarr doors are available with both 2" or 3" track in Standard Lift, High Lift, Vertical Lift, Low Headroom, and Follow the Roof Pitch. Custom track configurations are also available. For drawings and more information, please visit www.amarr.com.

Springs: Torsion springs are oil tempered, helical wound and custom computed for each door for a minimum 10,000 cycle life. Optional springs are available up to 100,000 cycle life.

Hardware: Amarr hardware includes minimum 14-gauge galvanized steel hinges and 13-gauge galvanized steel track brackets. All rollers have minimum 10-ball bearings.

SPECIFICATIONS

	Heavy-duty Amarr 2432 formerly Amarr 1000
STEEL THICKNESS (Front/Back)	24-ga / 27-ga
PANEL DESIGN	Pencil Groove
STEEL EMBOSSMENT	Stucco
DOOR THICKNESS	2" (5.1cm)
CONSTRUCTION LAYERS	Triple
INSULATION ¹	Polystyrene
R-VALUE ²	9.19
MINIMUM WIDTH	6'
MAXIMUM WIDTH	24' 2"
MINIMUM HEIGHT	7'
MAXIMUM HEIGHT	24' 2"
WIND LOAD ³ AVAILABLE	•
PAINT FINISH WARRANTY ⁴	10 Years
WORKMANSHIP/HARDWARE WARRANTY ⁴	1 Year

¹ Insulation has passed self-ignition, flamespread and smoke developed index fire testing.

² Calculated door section R-value is in accordance with DASMA TDS-163.

³ It is your responsibility to make sure your garage door meets local building codes.

⁴ For complete warranty details, visit amarr.com or contact your local Amarr dealer.

PANEL OPTIONS



PENCIL GROOVE PANEL WITH STUCCO EMBOSSMENT

WINDOW OPTIONS



24" X 12" INSULATED GLASS
Available with either a black or white frame.



24" X 6" DOUBLE INSULATED
ACRYLIC WINDOWS WITH BLACK FRAME

COLORS

Amarr steel doors are pre-painted; for custom colors, exterior latex paint must be used. Visit amarr.com for instructions on painting. Actual paint colors may vary from samples shown.



WHITE



SANDTONE



COMMERCIAL GRAY



COMMERCIAL BROWN



ENTRE/MATIC

Entrematic
165 Carriage Court
Winston-Salem, NC 27105
800.503.DOOR
www.amarr.com

FOR TECHNICAL
QUESTIONS:
1.866.366.4814



YOUR LOCAL AMARR DEALER: